



**SPECIFICATIONS**

- Submersible up to 15 ft / 5 m
- Manufactured from 14g Type 316 Marine Grade Stainless Steel (Material Code: **S**) as standard  
Optional Aluminum (Material Code: **A**)
- Seams continuously welded and dressed
- Single piece Neoprene gasket
- Minimum flange width to maximize internal capacity
- Mounting brackets on enclosure rear for direct wall mounting
- Grounding stud on body
- Mounting studs for optional internal mount plates
- #3 polish finish

**ACCESSORIES**

- Internal Mount/Back Plates
- External ground mounting stand
- Custom entry holes
- IP68 Stainless Steel cable glands / chord grips
- EMI / RFI Shielding (MIL-STD-285)
- Hinged Lid
- Welded in place Bosses
- Finish options available
- Shock & Vibration Protection (MIL-STD-810)

**INDUSTRY STANDARDS**

Engineered for NEMA Type 6P requirements  
(meets NEMA 4,4X,6P and IP68)

**APPLICATION**

SLAYSON Submersible **Standard Series** offers NEMA 6P / IP68 protection against water and dust ingress at depths up to 15ft / 5m. Submersible Standard Enclosures are manufactured as standard from 14g Marine Grade 316 Stainless Steel, ensuring protection in harsh and corrosive environments.

**MODIFICATION AND CUSTOMIZATION**

SLAYSON excels at modifying and customizing all our products to meet your exact specifications. Contact our experienced Engineers about your project specific solution.

**PART NUMBER MATERIAL CODE BUILDER**

**ASMI**—Type 316 Marine Grade Stainless Steel (14g)

**AAMI**—Aluminum (0.064")

PART NUMBER	A	B	C	D Mount	E Mount	BACK PLATE PART NUMBER	Height: in (mm)	Width: in (mm)	Gauge	Weight (lbs)
	Height: in (mm)	Width: in (mm)	Depth: in (mm)	Height: in (mm)	Width: in (mm)					
ASMI363624	36 (914.4)	36 (914.4)	24 (609.6)	32 (812.8)	38 (965.2)	ASPI3232	32 (812.8)	32 (812.8)	14	53
ASMI363612	36 (914.4)	36 (914.4)	12 (304.8)	32 (812.8)	38 (965.2)	ASPI3232	32 (812.8)	32 (812.8)	14	45
ASMI343424	34 (863.6)	34 (863.6)	24 (609.6)	30 (762)	36 (914.4)	ASPI3030	30 (762)	30 (762)	14	51
ASMI343412	34 (863.6)	34 (863.6)	12 (304.8)	30 (762)	36 (914.4)	ASPI3030	30 (762)	30 (762)	14	43
ASMI303018	30 (762)	30 (762)	18 (457.2)	26 (660.4)	32 (812.8)	ASPI2626	26 (660.4)	26 (660.4)	14	43
ASMI302618	30 (762)	26 (660.4)	18 (457.2)	26 (660.4)	28 (711.2)	ASPI2622	26 (660.4)	22 (558.8)	14	41
ASMI282816	28 (711.2)	28 (711.2)	16 (406.4)	24 (609.6)	30 (762)	ASPI2424	24 (609.6)	24 (609.6)	14	40
ASMI282416	28 (711.2)	24 (609.6)	16 (406.4)	24 (609.6)	26 (660.4)	ASPI2422	24 (609.6)	22 (558.8)	14	37
ASMI262614	26 (660.4)	26 (660.4)	14 (355.6)	22 (558.8)	28 (711.2)	ASPI2222	22 (558.8)	22 (558.8)	14	36
ASMI262214	26 (660.4)	22 (558.8)	14 (355.6)	22 (558.8)	24 (609.6)	ASPI2218	22 (558.8)	18 (457.2)	14	34
ASMI242412	24 (609.6)	24 (609.6)	12 (304.8)	20 (508)	26 (660.4)	ASPI2020	20 (508)	20 (508)	14	33